

Kaufmann Storm Windows

by **Styleline**

TWO TRACK COMBINATION STORM AND SCREEN

FEATURES

- Two track operation - screen is located below the upper sash in outer track.
- Fully weatherstripped frame - improves the insulation of existing windows resulting in energy cost savings for the Winter and the Summer.
- Protection for the prime window against the damaging effects of wind, rain and sunlight - House paint lasts 4 to 5 times longer.
- Aluminum screen with fiberglass screen cloth included.
- Sash and screen that are easily removed from the inside for cleaning.



Double Hung

- Standard 1" sill expander for sloped wood frame 1 1/2" expander for drop sill.
- Cottage or oriel style allows for meeting rail alignment with prime window.

Side Slider

- End vent or Center vent configuration.

Popular Options:

Low E Glass: clear glass with a thin metallic coating that reflects heat, and reduces harmful UV light. Low E glass doubles the insulating benefit of the storm window.

Sash reinforcement pins: are additional nylon clips located at the perimeter of the sash that prevent the sash from bowing away from the frame under wind load.

Finned weatherstrip: laser welded, polypropylene fin for reduced air infiltration.

Frame tie bar: An aluminum bar that helps to strengthen larger storm window frames.

Deluxe: Low E glass, sash reinforcement pins, finned weatherstrip and frame tie bar

QUALITY CONSTRUCTION

LONG SERVICE LIFE

- Zinc die cast sash retaining handles for strength.
- Continuous meeting rail interlock eliminates sash rattle and minimizes air infiltration.
- Nominal .050" thick walls of 6063-T5 extruded aluminum for durability.
- Large selection of models and configurations.

Ten popular colors :
White and Mill Finish
Almond - Sandstone - Bronze - Brown
Clay - Hunter Green
Black - Country Red

Made in the USA

Size Limitations	Minimum		Maximum		Maximum
	W	H	W	H	U.I.
Double Hung	12	18	52	84	132
Picture Window	12	12	60	60	120
2 lite slider	18	12	72	54	132
3 lite slider	27	12	96	54	155

All windows are made tip to tip (TTT) to exact sizes provided.
 Factory does not make any deductions or allowances.

U.I. - United Inch - Frame width rounded up to next full inch plus frame height rounded up to next full inch.